

BALAD²

3613 - LAMP H.10 IN.

DESIGN BY TRISTAN LOHNER



Polyethylene diffuser

Aluminum frame

ABS base

Technology: integrated LED - Luminous flux: 150 lm

Switch type: touch-activated dimmer

Function of the switch: change the brightness (10 to 100%, click 4 s),
change the light temperature (double short click), ON/OFF (short click, 1s)

Lighting mood:

Position 1 cool white (5000°K) dimmer switch (10 to 100%)

Position 2 warm white (3500°K) dimmer switch (10 to 100%)

Position 3 candle-style warm white (2200°K) flickering

Type of power supply: battery - Min. Battery life (100%) 8 h

Battery use cycle: 2000 cycles

Recharge time: 6h - Type of recharge: USB-C Fermob magnet – cable (provided) 59 in.

Bypass to prevent battery damage during wired use

0.48 A - 3,2 V - 3.5 W - IP54 | IK 10 | CE | FCC | UKCA

Powered by Smart & Green

Compatible with:

SPIKE STAND - BALAD²

UPRIGHT STAND - BALAD²



361347 Anthracite
361382 Cactus
3613A5 Clay Grey

3613E1 Maya Blue
3613E2 Candied Orange



BALAD², LUXEMBOURG & STRIPE



BALAD² & BISTRO