

3623 - LAMP H.15 IN.
DESIGN BY TRISTAN LOHNER

NEW RESIDENTIAL CONTRACT INTENSIVE 2 IREP IRCY 5



Polyethylene diffuser

Aluminum frame

ABS base

Technology: integrated LED - Luminous flux: 200 lm

Switch type: touch-activated dimmer

Function of the switch: change the brightness (10 to 100%, click 4 s),
change the light temperature (double short click), ON/OFF (short click, 1s)

Lighting mood:

Position 1 cool white (5000°K) dimmer switch (10 to 100%)

Position 2 warm white (3500°K) dimmer switch (10 to 100%)

Position 3 candle-style warm white (2200°K) flickering

Type of power supply: battery - Min. Battery life (100%) 10 h

Battery use cycle: 2000 cycles

Recharge time: 5h - Type of recharge: USB-C Fermob magnet – cable (provided) 59 in.

Bypass to prevent battery damage during wired use

0.65 A - 3.2 V - 6 W - IP54 | IK 10 | CE | FCC | UKCA

Powered by Smart & Green

Compatible with:

OFFSET STAND - BALAD²



2.38 lbs



- | | | | | | |
|--------|--|------------|--------|--|----------------|
| 362347 | | Anthracite | 3623E1 | | Maya Blue |
| 362382 | | Cactus | 3623E2 | | Candied Orange |
| 3623A5 | | Clay Grey | | | |



BALAD²



BALAD²