

YUNOS

3297 - SOLAR FLOOR LAMP H.71 IN.

DESIGN BY STUDIO FERMOB

NEW

RESIDENTIAL CONTRACT INTENSIVE

2 IREP

IRCY



Polyethylene diffuser

Aluminum frame

Technology: integrated LED – Luminous flux: 800 lm

Switch type: push button

Function of the switch: change of brightness (10 to 100%, click 4 s), change of light temperature (double short click), ON/OFF (short click, 1 s)

Lighting mood:

Position 1 cool white (5000°K) dimmer switch (10 to 100%)

Position 2 warm white (3500°K) dimmer switch (10 to 100%)

Automatic mode: as soon as the light level is ≤ 50 lux,

It switches on automatically thanks to its built-in brightness sensors.

It switches off as soon as the light level is ≥ 50 lux.

Type of power supply: solar and battery – Min. Battery life (100%): 10 h

Battery use cycle: 1000 cycles


Type of recharge: Solar or USB-C cable (provided) 98.4 in.

Bypass to prevent battery damage during wired use.

Protective cover included

2 A - 20 V - 9 W | IP54 | IK 3 | CE | FCC | UKCA

Powered by Smart & Green



3297A5 Clay Grey

329748 Rosemary

3297B9 Black Cherry

3297D2 Gingerbread



LIGHTING
IN & OUT